

' What is claimed is:

1. An image display system comprising:

a host for executing an application; and

a display connected to the host, the display displaying an image, wherein said host transfers undeveloped image data to the display when the host requests the display to display the image, and said display includes a panel memory for developing the image, develops the image in the panel memory based on the image data transferred from said host, and displays the image on its panel, which is developed in the panel memory.

2. The image display system according to claim 1, wherein said display refreshes said panel based on the image developed in said panel memory.

3. The image display system according to claim 1, wherein said host transfers image data showing a first resolution to said display based on an output from an application executed with the first resolution, and said display converts said transferred image data having the first resolution to that having a second resolution higher than the first resolution, and develops said image data for said panel memory.

25

4. The image display system according to claim 1, wherein

said host transfers compressed image data to said display as it is compressed, and said display expands said compressed image data transferred thereto, and develops said expanded image data for said panel memory.

5

5. An image display system comprising:

        a plurality of system devices for executing the same application; and

        a display device having panel controlling means for  
10 dividing a display area into a plurality of areas and  
        controlling driving of the divided areas, wherein the  
        plurality of system devices are connected to respective  
        panel control means provided in said display device, and  
        output first control signals for a synchronization with  
15 said display device to the respective panel control means;  
        and said panel control means in said display device outputs  
        a second control signals for a synchronization with said  
        display device to the system devices, based on the first  
        control signals outputted from said plurality of system  
20 devices.

6. The image display system according to claim 5, wherein  
    said first control signals outputted from said system  
    devices are job information which can be processed in a  
25 next frame by the system devices, and said second control  
    signals, which are outputted from said panel control means,

are information indicating a job which shows the lowest processing speed detected from said job information, which is outputted from said system devices.

5 7. The image display system according to claim 5, wherein said system device determines a job to be executed based on the second control signal outputted from said panel control means, and outputs image data to request a display of said display means by executing the job.

10

8. An image display system comprising:

a host for executing a plurality of applications showing different display characteristics and data quantities, which are required;

15 a display for displaying an image; and

a digital interface for transferring image data from said host to said display, wherein said digital interface changes a transfer format depending on an application executed by said host, and transfers image data to said 20 display, and said display develops said image data transferred via said digital interface in a panel memory for developing, and then displays an image on a panel.

25 9. The image display system according to claim 8, wherein said digital interface transfers said image data by a packet, and transfers said image data by specifying a data

transfer mode in the packet, and said display develops said image data in said panel memory based on said data transfer mode specified.

5 10. A host device comprising:

executing means for executing a plurality of applications having different display characteristics and data quantities, which are required;

10 window managing means for managing a window ID defined for a window that is an area which makes definite sense in an image space, of which said application is conscious; and  
image data transfer means for adding the window ID managed by said window managing means to undeveloped image data, for which said application requests a display, and  
15 transferring the undeveloped image data.

11. The host device according to claim 10, wherein said image data transfer means transfers said image data in the form of a packet, and transfers said image data after  
20 changing a transfer style of the image data depending on the application.

12. A host device comprising:

image transfer means for transferring image data to a  
25 display connected thereto; and  
control means for supplying image data to said data

transfer means based on an executed application of a still picture and an executed application of a moving picture, wherein said control means supplies the image data regardless of refresh timing required for said display with respect to the application of said still picture, and supplies the image data in synchronization with refresh timing required for said display with respect to the application of said moving picture.

10 13. An image display device comprising:

a panel for displaying an image;

image data receiving means for receiving undeveloped image data from a host device which executes an application;

15 a panel memory for developing said image data received from said image data receiving means; and

panel control means for developing image data for said panel memory and writing a developed image for said panel.

20 14. The image display device according to claim 13, wherein said image data receiving means receives a plurality of undeveloped image data showing different display characteristics and data quantities, which are required, and said panel control means develops said plurality of undeveloped image data, thus forming a display screen.

15. The image display device according to claim 13, wherein  
said panel control means executes refreshing for said panel  
based on the image data developed in said panel memory.

5   16. The image display device according to claim 13, wherein  
said image data receiving means receives image data having  
a first resolution, and said panel control means scales  
said image data to a second resolution different from said  
first resolution, and develops said image data for said  
10 panel memory.

17. An image display device which is connected to a plurality  
of system devices for executing the same job, and  
displays an image based on image data transferred from the  
15 plurality of system devices, comprising:

      a display section for displaying the image, either as  
panels divided into a plurality of display areas or as one  
panel obtained by collecting a plurality of display panels;  
and

20       one or more panel control means for controlling an  
image display of said display section, wherein said panel  
control means receives a control signal concerning a job  
from said plurality of system devices, and transmits a  
control signal used for achieving synchronization of the  
25 system devices to said plurality of system devices.

18. The image display device according to claim 17, wherein  
said plurality of panel control means are provided, each of  
which corresponds to corresponding one of said divided  
panels in said display section or to corresponding one of  
5 said display panels constituting the plurality of display  
panels as one panel, and an internal bus for allowing other  
panel control means to recognize said control signal  
received by specified control means is further provided.

10 19. The image display device according to claim 18, wherein  
said control signal received by said control means is a job  
number executable in a next frame by said system device,  
and said control means transmits a control signal including  
a job number to be executed in the next frame by said  
15 system device, based on the job number on said bus.

20. An image display device comprising:  
a panel for displaying an image;  
image data receiving means for receiving undeveloped  
20 image data from a host side which executes a plurality of  
applications;  
a panel memory for developing said image data received  
from said image data receiving means; and  
panel control means for developing image data for said  
25 panel memory and performing a color adjustment for each  
image data, each image data transferred by one of said

different applications, thus writing an image to said panel.

21. An image display device comprising:

5        a panel for displaying an image;

image data receiving means for receiving color image data of the first number of bits and monochrome image data of the second number of bits different from the first number of bits from a host side;

10      a panel memory for developing said image data received from said image data receiving means; and

panel control means for developing image data for said panel memory, wherein said panel control means develops said color image data and said monochrome image data, which 15 are received from said image data receiving means, in said panel memory, the color image data and said monochrome image data being developed in different data formats.

22. The image display device according to claim 21, wherein

20     said panel control means writes identification bits for discriminating between said color image data and said monochrome image data, and executes a developing processing based on the identification bits.

25    23. An image display method for displaying an image on a display connected to a host, based on a signal from the

host which executes an application, comprising the steps of:

transferring undeveloped image data for an image display from said host to said display via a digital  
5 interface;

developing said transferred image data by said display itself, for a memory of said display; and

displaying an image developed in said memory on said display.

10

24. The image display method according to claim 23, wherein refreshing of said display is performed based on said image developed in said memory of said display.

15

25. An image display method for displaying an image on a display connected a host, based on a signal from the host which executes an application, comprising the steps of:

20

transferring image data showing a first resolution executed by said application from said host to said display;

scaling the image data showing the first resolution by said display, which is transferred from said host;

developing an image with a second resolution different from said first resolution; and

25

outputting the image to a panel of said display so as to display the image on the panel.

26. The image display method according to claim 25,  
wherein said display is a multi-panel obtained by  
tiling a plurality of panels or a high-resolution panel;  
5 and  
scaling of said image data is an enlarged display.